

Table 3

Bore DN (mm)	Model	Measuring range		Accuracy class	Taper pipe length (mm)	State of the liquid allowed	
		Water, 20℃	Air, 20℃, 101325Pa			Temperature(℃)	Pressure(MPa)
3	LZB-3W LZB-3WB	0.4 ~ 4 ml/min	6 ~ 60 ml/min	4	100	0 ~ 60	≤ 0.2
		0.6 ~ 6 ml/min	10 ~ 100 ml/min				
1 ~ 10 ml/min	16 ~ 160 ml/min						
1.6 ~ 16 ml/min	25 ~ 250 ml/min						
4	LZB-4W LZB-4WB	2.5 ~ 25 ml/min	40 ~ 400 ml/min	2.5	120	0 ~ 60	≤ 0.2
		4 ~ 40 ml/min	60 ~ 600 ml/min				
		6 ~ 60 ml/min	100 ~ 1000 ml/min				
6	LZB-6W LZB-6WB	10 ~ 100 ml/min	160 ~ 1600 ml/min	2.5	120	0 ~ 60	≤ 0.2
		16 ~ 160 ml/min	0.3 ~ 3 L/min				
10	LZB-10W LZB-10WB	25 ~ 250 ml/min	0.6 ~ 6 L/min	2.5	120	0 ~ 60	≤ 0.2
		40 ~ 400 ml/min	0.7 ~ 7 L/min				
		0.04 ~ 0.4 L/min	0.7 ~ 7 L/min				
10	LZB-10W LZB-10WB	0.06 ~ 0.6 L/min	1 ~ 10 L/min	2.5	120	0 ~ 60	≤ 0.2
		0.1 ~ 1 L/min	1.5 ~ 15 L/min				
10	LZB-10W LZB-10WB	0.1 ~ 1 L/min	3 ~ 30 L/min	2.5	120	0 ~ 60	≤ 0.2
		0.16 ~ 1.6 L/min	5 ~ 45 L/min				

Note: Special flow measurement range should be indicated separately.